

# AGP151

JAMMA-Type Gaming Control System with 12th Gen Intel® Core™ Processor (Codename: Alder Lake-S)

## Features

- Intel® Alder Lake-S series processor
- 2x sockets of DDR4 SODIMM 260 pins
- PCIe x16 expansion
- 2x SATADOM, 1x CFast, 1x M.2 (PCIe x4)
- Supports TPM2.0 & Secure BIOS
- 1x VGA, 2x HDMI, 1x DP++
- 72-pins JAMMA interface
- Supports 4ch LED strip, up to 4000pcs LED chips
- 6W+6W Audio amplified output



## Specification

CPU	JAMMA-type gaming system with Intel® Alder Lake-S processor, TDP 65W Option1: Pentium® processor G7400TE, 4 cores, 3.0GHz, DP 35W Option2: Celeron® processor G6900TE, 2 cores, 2.4GHz, DP 35W Option3: i7-12700E/ i5-12500E/ i3-12100E (by request)
Chipset	Support H610, Q670
Memory	2x DDR4-3200, 260-pin SO-DIMM Max up to 64GB
Graphic	1x VGA. D-Sub15 connector 2x HDMI 1x DP++ (Q670) DirectX 12.1 compliant, OpenGL ES 3.1, OpenGL 4.6, OpenCL™ 1.2
Security	AMI BIOS Secure BIOS & storage integrity, by request TPM 2.0 on board (option)
Storage	2x SATA DOM, support pin-7 power 1x vertical CFast socket (option) 1x M.2 M-key (PCIe x4) NVMe supported
Expansion	1x PCIe x16 slot
USB	USB 3.2 - 2x external type-A connector - 1x Internal vertical Type-A connector USB 2.0 - 2x external type-A connector - 2x external type-A connector (Q670)
COM Port	6x COM port - 1x Full COM DB9 connector (COM1) support RS232/422/485 - 1x Full COM DB9 connector (COM2) support RS232/TTL - 2x Full COM DB9 connector (COM3, COM4) support RS232/ccTalk - 2x simple COM by pin header or JAMMA 72-pin golden finger

Audio	5.1-ch audio output by jack connector 6W + 6W (R/L) class-D amplified output by JAMMA 72-pin
LAN	2x ethernet GbE by RJ45 connector
Gaming I/O	Intrusion type - 2x by internal pin header - 6x by JAMMA 72-pin SRAM / MRAM(battery-less backup) - 2x bank supported with battery backup, support up to 8MB, 16MB by request - Default 4MB (2 bank) DI/DO - 27x bits isolated digital input - 27x bits high current output. 0.5A/30V Tachometer - 2x fan speed detection Event log - Up to 200 event logs EEPROM - Default 1KB Low battery warning for SRAM and intrusion - 2x low battery detection LED strip control - 4ch LED strip support - Support up to 4000 LED
Indicator	Power, HDD, Low Bat
OS	Windows Linux
Power	DC+12V / DC+24V Power failure detection
EMC	CE/FCC Class A
EDS	Air: -/+ 8kv criteria B, Contact: -/+4kv criteria B
Environment	Operation temperature: 0°C ~ +40°C Storage temperature: -20°C ~ +80°C Humidity: 10%RH ~ 95%RH relative humidity (non-condensing)
Dimension	329.4mm(W) x 192.6mm(D) x 56.3mm(H)

\* All specifications and photos are subject to change without notice.

For more information please contact: gaming@axiomtek.com.tw No. 3130-1401801